

NEC UM301WG

Order Code: NP-UM301WG

NEC Professional Ultra-Short-Throw Projector



Get great performance while saving the environment. Advanced Eco features help to substantially lower your operating cost without compromising on quality and flexibility. Less shadow and glare gives the presenter more space to engage with his audience and enhances the experience with interactive white boards.

The UM301W is particularly suited for classrooms and small to medium sized meeting rooms.

BENEFITS

No Shadow and Glare thanks to ultra-short throwing distance - for an enhanced interactive whiteboard experience and more space to engage with your audience when presenting.

Minimized Cost of Ownership - due to long lamp life and lower power consumption.

Innovative new Eco functions - to reduce power consumption.

Optional Multi-pen Interactivity - with real gesture support on any kind of surface.

Future proof connectivity - due to numerous analog and digital connection terminals including MHL support, network capability as well as optional wireless connectivity.

Wall-mount included - for quick and easy installation, compatible with height adjustable systems.

NEC Factory Preset
DICOM
SIMULATION



HDMI
HIGH DEFINITION MULTIMEDIA INTERFACE

IMAGE	Projection Technology	3 x 1.5 cm (0.59") p-Si LCD Panel with MLA
	Native Resolution	1280 x 800 (WXGA)
	Aspect Ratio	16:10
	Contrast Ratio ¹	4000:1
	Brightness ¹	3000 ANSI Lumen (approx. 75% in Normal, 60% in Eco Mode)
	Lamp	235 W High Bright / 170 W Normal / 140 W Eco Mode
	Lamp Life [hrs]	8000 Eco / 5000 Normal / 4000 High Bright Mode
	Lens	F= 1.8, f= 4.78 mm
	Projection Factor	0.36 : 1
	Projection Distance [m]	0.11 – 0.51
	Projection Angle [°]	49.2
	Screen Size (diagonal) [cm] / [inch]	Maximum: 279.4 / 110"; Minimum: 147.3 / 58"
	Zoom	1.4 x Digital Zoom
	Focus Adjustment	Manual
	CONNECTIVITY	Supported Resolutions
Frequency		Horizontal: 15–100 kHz (RGB: 24 kHz– 100 kHz); Vertical: 50 – 120 Hz
RGB (analog)		Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr) Output: 1 x Mini D-sub 15 pin
HDMI™		Input: 1 x HDMI™ (Deep Color, Lip sync); 1 x HDMI™ with MHL support
Video		Input: 1 x RCA
Audio		Input: 1 x 3.5 mm Stereo Mini Jack; 1 x RCA Stereo Output: 1 x 3.5 mm Stereo Mini Jack (variable)
Microphone		Input: 1 x 3.5 mm Stereo Mini Jack (Dynamic mic)
Control		Input: 1 x D-Sub 9 pin (RS-232) (male)
LAN		1 x RJ45; Optional WLAN
USB		1 x Type B; 2 x Type A (USB 2.0 high speed)
REMOTE CONTROL	Remote Control	Aspect Ratio; Audio Control; Auto Adjust; AV Mute; Digital Zoom; Direct Source Select; Freeze; Help Eco Mode; Help-function; ID set; Picture Adjust; Presentation and Mouse Control
ELECTRICAL	Power Supply	100-240 V AC; 50 - 60 Hz
	Power Consumption [W]	234 (Normal) / 196 (Eco) / 8 (Network Stand-by) / 0.4 (Stand-by); 297 (High Bright)
MECHANICAL	Dimensions (W x H x D) [mm]	378 x 112 x 428 (without lens and feet)
	Weight [kg]	5.5
	Fan Noise [dB (A)]	27 / 27 / 35 (ECO / Normal / High Bright)
ENVIRONMENTAL CONDITIONS	Operating Temperature [°C]	5 to 40
	Operating Humidity [%]	20 to 80 non-condensing
	Storage Temperature [°C]	-10 to 50
	Storage Humidity [%]	20 to 80 non-condensing
ERGONOMICS	Safety and Ergonomics	CE; Gost-R; RoHS; TÜV GS
	Speakers [W]	1 x 20 (mono)
ADDITIONAL FEATURES	Special Characteristics	AMX Beacon; Auto Eco Mode; Auto Power ON/OFF; Carbon Savings Meter; Colour Management; Content Transmission via Network; Contrast Ratio 4000:1 with Iris; Crestron RoomView; DICOM Simulation; Direct Power-Off Function; High Altitude Mode; Kensington security slot; Keypad Lock; Magnify; Manual vertical Keystone Correction (V= ±10°); NaViSet Administrator 2; Off-Timer; Optional User Logo; Optional WLAN; OSD with 29 languages; Password Security System; PJ LINK; Quick On/Off; Remote control and administration via LAN and RS232; Security Bar; Test Pattern; USB Display; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction
GREEN FEATURES	Energy Efficiency	75 % AV mute function; Auto ECO Mode; ECO scheduler; Green one touch ECO and AV mute button; Intelligent Power Management; Longer lamp life; Reduced power consumption. Only 0.4W stand-by; Software scheduling
	Ecological Materials	100% recyclable packaging; Downloadable manuals; ECO packaging
	Ecological Standards	ErP compliant; RoHS compliant
WARRANTY	Projectors	5 years conditional warranty
	Lamp	6 months, max 2,000 hours
SHIPPING CONTENT	Shipping Contents	IR Remote Control (RD-448E); Mini D-SUB Signal Cable; Power Cord (1.8 m); Quick Setup Guide; Security Sticker; Users Manual on CD-ROM; Wall-mount kit NP04WK
OPTIONAL ACCESSORIES	Optional Accessories	DisplayNote; Interactive Unit (NP03Wi); Lamp (NP32LP); Wireless LAN module (NP02LM2)

¹ Compliance with ISO21118-2005

For more information, visit au.nec.com, email contactus@nec.com.au or call 131 632

Australia
NEC Australia Pty Ltd
au.nec.com

Corporate Headquarters (Japan)
NEC Corporation
www.nec.com

North America (USA)
NEC Corporation of America
www.necam.com

Asia Pacific (AP)
NEC Asia Pacific
sg.nec.com

Europe (EMEA)
NEC Enterprise Solutions
www.nec-enterprise.com

Product | v1.24.03.2015

NEC Australia Pty Ltd reserves the right to change product specifications, functions, or features, at any time, without notice. Please refer to your local NEC representatives for further details. Although all efforts have been made to ensure that the contents are correct, NEC shall not be liable for any direct, indirect, consequential or incidental damages resulting from the use of the equipment, manual or any related materials. The information contained herein is the property of NEC Australia Pty Ltd and shall not be reproduced without prior written approval from NEC Australia Pty Ltd.

Copyright © 2015 NEC Australia Pty Ltd. All rights reserved. NEC, NEC logo, and UNIVERGE are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All other trademarks are the property of their respective owners. All rights reserved. Printed in Australia. Note: This disclaimer also applies to all related documents previously published.

Empowered by Innovation

